

# Hottaping and pigging solutions

EPROX provide all materials and services for hottaping

and pigging through our top European partners.

# Hottaping

Eprox , has a "Hot-Tap & Line Stop Division" to provide no-shutdown piping solutions to customers, we strongly believe that our developing on the unique Hot Tap and Line Stop fittings, equipment and services will provide the best and most cost effective solution to the specific project need.













EPROX provides standard pigging, Our pipeline pigging program consist the manufacture of poly foam pigs, decoking pigs, moni-directional pigs fitted with cups (standard scraper or conical) and bi-directional pigs fitted with discs (soft sealing, hard guiding) and custom made pigs starting at size 2" upto 100" for poly foam pigs and size 4" upto 60".

#### **HOT TAP/LINE STOP TEE FEATURES:**



- -Full branch or reduced branch fittings for use in Hot Tapping /Line Stopping operations
- -Supplied with ASME Class 150, 300, 600, 900, 1500 flanges with RF or RTJ.
- -Other flange classes available on request
- -Tee available with a butt weld outlet, ready to be welded to a valve or other fitting
- -Standard fittings meet the requirements of ASME B31.3 and ASME B31.4/B31.8 with a 0.72 design factor
- -Compatible with all major models of hot tapping /Line Stopping equipment
- -All pressure containing welds are 100% radiographed
- -Back-up strips available
- -Manufactured in compliance with ISO 9001:2015 certified quality program



### Sandwich Valves

We manufacture and Supply 3 Inch to 60 Inches of 150 / 300/ 600 Class Pressure Ratings. For above 60 Inches and above 600 Class Pressure ratings kindly contact us



# Line Stop Housingg

We manufacture and Supply 3 Inch to 60 Inches of 150 / 300/ 600 Class Pressure Ratings. For above 60 Inches and above 600 Class Pressure ratings kindly contact us.

## **Line Stop Actuators**





### Line Stop Heads

We manufacture and Supply 3 Inch to 60 Inches of 150 / 300/ 600 Class Pressure Ratings. For above 60 Inches and above 600 Class Pressure ratings kindly contact us.

#### **Line Stop Sealing Elements:**

- Supplied Ready Drilled and ground to size or drilled and unground depending upon customer's requirement
- Available in Sizes from 4 to 60 Inches
- Available with NBR, EPDM, Viton and Polyurethane material
- Reinforced for High Pressure applications